

# Handheld Tyre Inflators

## DTI

This handheld digital electronic tyre inflator is easy and cost effective to use offers reliable accuracy (+/- 1 psi up to 60 psi, then 2 psi up to 150 psi).

- Large, clear, easy to read LCD display with backlight
- PSI/BAR/kPa units selector switch
- Backlight on/off switch



Part Number	Hose Length	Tyre Valve Connection	Calibration
DTI081	0.5 m	Euro Clip-on	5-170 psi
DTI091THO	0.5 m	Twin Hold-on	5-170 psi

## ACCURA 1

ACCURA 1 offers fast, accurate and trouble free tyre inflation and deflation.

- Ceramic sensor and a clear and easy to read digital display
- Complies with EC Directive 86/217/ EEC & BS EN 12645: 1999



Part Number	Hose Length	Tyre Valve Connection	Calibration
DAC1A03	0.53 m	Twin hold-on	0-174 psi
DAC1A06	2.7 m	Twin clip-on	0-174 psi
DAC1A08	1.8 m	Euro Clip-on	0-174 psi

## TI

The robust yet economical handheld analogue tyre inflator for fast tyre inflation/deflation.

- Modern, lightweight and shock resistant construction
- Dial with PSI/BAR units
- Least count: 2 psi
- Calibration 0-174 psi/ 0-12 bar



Part Number	Hose Length	Tyre Valve Connection
TI0014C	0.5 m	Euro Clip-on
TI0014THO	0.5 m	Twin Hold-on

## Alloy Tyre Inflator



A general purpose tyre inflator with an all Alloy body with a rubber protected analogue gauge.

- Durable alloy body and Euro style valve connector
- Ideal for general low volume tyre inflation
- Least count: 2 psi / 0.1 bar

Part Number	Hose Length	Tyre Valve Connection	Calibration
ADTG4	0.85 m	Euro Clip-on	10-210 psi / 0.7-15 bar

## Airforce Tyre Inflator



This robust, lightweight handheld and shock resistant mechanical tyre inflator offers fast, trouble free tyre inflation.

- Guaranteed accuracy - individual testing
- Least count: 2 psi / 0.1 bar
- Complies with EC Directive 86/217/EEC & BS EN 12645
- Long product life

Part Number	Hose Length	Tyre Valve Connection	Calibration
AFG1H03	0.53 m	Twin hold-on	0-170 psi / 0-12 bar
AFG1H06	2.7 m	Twin clip-on	0-170 psi / 0-12 bar
AFG1H08	1.8 m	Euro clip-on	0-170 psi / 0-12 bar

## Blowgun Style Tyre Inflator



A general purpose tyre inflator with an all Alloy body with a rubber protected analogue gauge.

- Durable alloy body and Euro style valve connector
- Simple and easy to use
- Ideal for general low volume tyre inflation
- Least count: 2 psi / 0.1 bar

Part Number	Hose Length	Tyre Valve Connection	Calibration
LTG01	0.4 m	Euro Clip-on	0-220psi / 0-15 bar

## AIRFORCE® MK4 Tyre Inflator



The already highly regarded predecessor to the AIRFORCE® MK4, the classic MK3 Tyre Inflator has been industry standard in many garages, petrol forecourts & tyre depots for over 25 years.

- Lighter Weight - Gauge body weighs 923g, less work strain and easier for repetitive use
- Aluminium body with impact absorbing rubber bumper
- Magnified scale
- Complies with EC Directive 86/217/EEC & BS EN 12645:2014

Part Number	Hose Length	Tyre Valve Connection	Calibration
AFG4H03	0.53 m	Twin hold-on	0-138 psi / 0-9.6 bar
AFG4H04	0.53 m	Single clip-on	0-138 psi / 0-9.6 bar
AFG4H05	1.8 m	Twin clip-on	0-138 psi / 0-9.6 bar
AFG4H08	0.53 m	Euro clip-on	0-138 psi / 0-9.6 bar
AFG5H36	3.6m	Twin clip-on	0-174 psi / 0-12 bar

## AIRFORCE® High Pressure MK4 Tyre Inflator



The High Pressure Tyre Inflator is robust yet lightweight and are available with dual scale calibration and offer guaranteed accuracy.

- Safe, cost-effective and trouble-free high pressure tyre inflation
- Reduced operating costs with fast inflation and deflation rates
- Excellent shock resistance with robust durable design and construction

Part Number	Hose Length	Tyre Valve Connection	Calibration
AFG6H04	1.8 m	Single clip-on	45-300 psi / 3-21 bar
AFG6H041	1.8 m	Twin clip-on	45-300 psi / 3-21 bar
AFG6A02	2.0 m	8v1 screw-on	-
AFG6A03	2.0 m	12v1 screw-on	-

### Contact us:

**Head office:**  
PCL-SUMO Air Technology Pvt Ltd

425 Gemstar Commercial Complex  
Ramchandra Lane Extension  
Kachpada  
Malad West  
Mumbai 400064  
India

sales@pclsumo.com  
T +91 (0)8080907242 / 8080208578  
F +91 (0)22 2881 9841 / 2242108899

**Main Service Centre: Vasai**  
west@pclsumo.com

pclservice@pclsumo.com  
prod@pclsumo.com  
T +91 9595107242 / 9320771607/08

**North/East Regional Office: New Delhi**

north@pclsumo.com  
T +91 1129534271/1498  
+91 9313733558  
F +91 1129531498

**South Regional Office: Chennai**

south@pclsumo.com  
T +91 4442039027  
+91 9381748386  
F +91 4442039022