

ACCURA QUBE



The simple and user friendly ACCURA QUBE Tyre Inflator proves that being square can be stylish.



The ACCURA QUBE is just as reliable and straight forward as all PCL's leading ACCURA product range, yet features just three modes: standard inflate/deflate, tyreshop (featuring over pressure). All that the customer needs to do is preset the required pressure, place the connector on the tyre and let the in-built auto-start function do the rest.

The unit's durable ceramic sensor allows extremely precise measurement

with tolerances well above the industry standard. Meanwhile the proven electronics and stable software mean low operating and maintenance costs. This 150 x 150 mm unit is designed to be simple and space-saving, without the programmability or customisation of the more expensive models. This versatile little unit is ideal for indoor use, particularly in commercial environments where ease of use and accuracy are key.



Key benefits For the Operator:

- Consistent cost effective provision of high levels of safe air inflation services.
- Low life time costs- long product life with robust design and proven electronics.
- Plug and play - tyre inflator with 3 pre-selectable application modes.
- Fits all applications - tyreshop, Automobile Service Centre, Forecourts, etc.
- Low and simple maintenance.
- Guaranteed accuracy with individual testing.

Key features

- Electronic pressure preset.
- Auto-start inflation.
- Touch screen technology.
- Clear display for easy customer usage.
- Space-saving and lightweight design.
- Robust, high reliability engineering plastic housing.
- Ceramic sensor - accuracy to +/- 0.5% of full scale reading.
- 230v, 100v/120v (USA only) and 12v versions.
- Can inflate accurately with higher length hoses.
- With moulded AC power cord for geographic regions.

Product Code

QUBE

Dimensions	150 x 150 x 92 mm
Weight	2.3 kg
Operating Temperature	-20 °C to 70 °C
Maximum Voltage	230 Vac
Accuracy	± 0.5% of full scale reading
Reading Accuracy	0.1 bar / 1 psi / 5 kPa
Flow Rate	2500 L/min@10 bar supply
Maximum Inlet Pressure	15 bar / 217 psi / 1500 kPa / 15.3 kg/cm ²
Maximum Inflation Pressure	145 psi / 10 bar / 1000kPa /10.2 kg/cm ²
Complies to	EMC-directive basis exceeds EC Directive 89/336/EEC

PCL-SUMO

AIR TECHNOLOGY PVT. LTD.

[A Joint Venture of PCL-UK (HORNGROUP) & Sumo Hi-Tech, India]

NORTH Phone : 011-29534271

SOUTH Phone : 044-42039027

WEST Phone : 022-42108888

Email : sales@pclsumo.com/ info@pclsumo.com

Website : www.pclsumo.com / www.pclairtechnology.com

Head Office : 424, Gemstar Commercial Complex,
Ramchandra Lane Extn., Kachpada, Malad (W),
Mumbai - 400 064. MAHARASHTRA. INDIA.

Tel : +91-22-4210 8888 **Telefax** : +91-22-42108899

Works : D-102, Prasad Industrial Estate, Sativali,
Vasai (E), Dist. Palghar - 401 208, Maharashtra, INDIA
Cell : 09320771602/06/07/08 **E-mail** : prod@pclsumo.com