

# Digital Auto Multi Tyre Inflator

PCL-SUMO's DTMI/D10 comes fitted in a portable Aluminium Die-Cast Casing.

PCL-Sumo Digital (D10), in Aluminium Die-Cast Casing is an automatically operating tyre pressure inflator with pre-selection of the required values via +/- keys. The actual and required values are indicated in Dual Display 30mm backlit transfective Liquid Crystal Display (LCD).

The adjusted value will be automatically reached after connection to a tyre. An acoustic signal is given when the nominal/required value is reached.

**We supply four tyre top-up Inflator with Air/N2 consisting of following items:**

- Powder coated MS fabricated Air Cabinet
- D10 Inflator with multi tyre programme
- Legris 'Stop/Fill' Valve
- Air Manifold/QRC
- Four numbers Nylon braided PVC hoses with end fittings and heavy duty close-end connectors, each hose 7.5 meter long
- Air Filter & Inlet Air pressure gauge



Dimensions	300 x 420 x 90 mm	
Max. Power during operation	18VA	
Voltage	230Vac	12V Car Battery
Max Inlet Air Supply Pressure	16 bar	232 psi
Max Inflation Pressure	10.7 bar	155 psi
Max Inflation Flow	1600 LPM @ 10 bar	
Accuracy	+/- 0.5% of full scale reading	
Reading Accuracy	0.1 bar	1 psi
Temperature range	-20 °C to 70 °C	
Standards Complied	EC-directive electromagnetic compatibility (89/336/EEC)	

**Contact us:**

**Head office:**  
PCL-SUMO Air Technology Pvt Ltd

425 Gemstar Commercial Complex  
Ramchandra Lane Extension  
Kachpada  
Malad West  
Mumbai 400064  
India

sales@pclsumo.com  
T +91 (0)8080907242 / 8080208578  
F +91 (0)22 2881 9841 / 2242108899

**Main Service Centre: Vasai**  
west@pclsumo.com

pclservice@pclsumo.com  
prod@pclsumo.com  
T +91 9595107242 / 9320771607/08

**North/East Regional Office: New Delhi**

north@pclsumo.com  
T +91 1129534271/1498  
+91 9313733558  
F +91 1129531498

**South Regional Office: Chennai**

south@pclsumo.com  
T +91 4442039027  
+91 9381748386  
F +91 4442039022